REFERENCES

- Mamtani R, Al-Thani MH, Al-Thani AA, Sheikh JI, Lowenfels AB. Motor vehicle injuries in Qatar: time trends in a rapidly developing Middle Eastern nation. *Inj Prev*. 2012 Apr;**18**(2):130–2. doi: 10.1136/injuryprev-2011-040147. Epub 2011 Oct 12.
- Consunji RJ, Peralta RR, Al-Thani H, Latifi R. The implications of the relative risk for road mortality on road safety programmes in Qatar. *Inj Prev*. 2015 Apr;**21**(e1):e105–8. doi: 10.1136/injuryprev-2013-040939. Epub 2014 Jan 28.
- World Health Organisation. Global status report on road safety 2015: supporting a decade of action: summary 2015.
- Sivak M, Schoettle B. Mortality From Road Crashes In 193 Countries: A Comparison With Other Leading Causes Of Death. The University of Michigan Transportation Research Institute. Report No. UMTRI-2014-6 February 2014.
- A Bener, T Lajunen, T Ozkan, D Haigney. "The Effect of Mobile Phone Use on Driving Style and Driving Skills." *International Journal of Crashworthiness* 2006;**11**(5):1–7.

869

ROAD TRAFFIC INJURIES IN KENYA: A HOSPITAL-BASED SURVEILLANCE STUDY

¹Isaac M Botchey, ¹Yuen W Hung, ¹Huan He, ¹Abdul M Bachani, ²Hassan Saidi, ¹Adnan A Hyder, ^{1,3}Kent A Stevens. ¹Johns Hopkins International Injury Research Unit, USA; ²University of Nairobi, Kenya; ³Johns Hopkins Hospital Department of Surgery, USA

10.1136/injuryprev-2016-042156.869

Background Road Traffic Injuries (RTIs) are a leading cause of disability and mortality worldwide with a disproportionate burden in Low-and Middle-Income Countries (LMICs). RTIs account for 3.6 percent of the global mortality burden [1]. Additionally, the risk of death from injuries in LMICs is six times more likely than in High Income Countries (HICs)[2]. RTIs are estimated to be the fifth leading cause of disability-adjusted life-years (DALYs) lost by 2030 worldwide[3]. Data defining the burden of injury, risk factors and outcomes of RTIs in LMICs are limited. Our study analyses RTIs seen in the casualty departments at four regional referral hospitals in Kenya.

Methods Electronic-based trauma registries were developed at four regional hospitals in Kenya: Kenyatta National, Thika, Meru and Machakos. Information on mechanism of injury, injury severity, patient outcomes, and patterns of care (pre-hospital and hospital-based) was collected prospectively between January 2014 to September 2015.

Results A total of 6429 patients were enrolled. Patients were predominantly male (78.5%), young (median age 27.6 years) and arrived mainly by car/taxi (49.4%), mini bus (18.9%) or an ambulance (16.2%). Injuries were common amongst pedestrians (40.8%) and passengers (36.7%). Seatbelts were used by 7.2% of passengers. Body regions most commonly injured were the extremities (54%) and head (22.7%). The overall mortality rate was 2.2%. Predictors of RTI deaths were moderate head injury [GCS 9–12] (OR 6.4, 95% CI: 4.0–10.1), severe head injury [GCS ≤ 8] (OR 71.5, 95% CI: 49.7–102.8), moderate ISS [ISS 9–15] (OR 3.6, 95% CI: 2.5–5.1) and severe ISS [ISS > 15] (OR 9.4, 95% CI: 5.7–15.2).

Conclusions RTIs contribute significantly to the burden of disease in Kenya. A renewed focus on addressing this burden through the development of a trauma care system is necessary. Trauma registries can be used as a plausible tool to identify priority areas for quality improvement and injury prevention.

870

BICYCLE ACCIDENTS: A NEW TREND FOR HOSPITAL ADMISSIONS?

Ricardo Mexia, Emanuel Rodrigues. Instituto Nacional De Saúde Doutor Ricardo Jorge, Portugal

10.1136/injuryprev-2016-042156.870

Background Bicycle riding is an increasing trend in many countries, so accidents connected with cycling activities are also on the rise.

Data from the National Agency for Road Safety shows that in 2013 there were 1708 victims in accidents where a bicycle was involved, rising from 1405 in 2003.

While most accidents are not reported and do not require healthcare, more severe ones can be a cause for admission in Hospitals. Limb injuries are the most frequent, but chest/abdomen injuries and head injuries are also common.

Methods Data was collected from the Portuguese National Hospital Registry (GDH), where all admissions to hospitals in Portugal are registered and coded with ICD9 codes. We gathered data on all admissions, external cause admissions and admissions for ICD9 E826 code (Pedal cycle accident). We compared data between 2003 and 2013 from all hospitals in Portugal.

Results Between 2003 and 2013 there were a total 7170 admissions for bicycle related accidents (651 average each year).

In 2003 there were 652 admissions related to bicycling accidents, while in 2013 there were 725 (an 11% increase). Male patients account for 83,4% of those admissions in 2003 and 87,0% of those in 2013. When compared to the total external cause admissions, bicycle related admissions represent 0,57% in 2003 and 0,42% in 2013 (a 25,6% decrease). Comparison on proportions for total admissions also presents a 30,0% decrease: from 0,060% in 2003 to 0,043% in 2013.

Conclusions During the last 10 years there has been an increase in the total number of hospital admissions connected with bicycle accidents and injuries. Potential explanations include an increase in cycling as a radical sport (such as mountain biking or downhill riding) and as daily mean of transportation (mostly in the urban setting), but further studies are required.

871

BUILT ENVIRONMENT ANALYSIS FOR ROAD TRAFFIC HOTSPOT LOCATIONS IN MOSHI, TANZANIA

¹Meredith Waldon, ²Treasure Joelson, ³Luciano Andrade, ¹Joao Ricardo N Vissoci, ²Mark Mvungi, ¹Catherine Staton. ¹Duke University, Durham USA; ²Kilimanjaro Christian Medical Centre, Tanzania; ³Unioeste. Foz Do Iguaçu, Brazil

10.1136/injuryprev-2016-042156.871

Background Road traffic injuries (RTI) are a significant cause of morbidity and mortality in low and middle income countries (LMIC). Further investigations of the high risk areas for RTIs in LMIC are needed to guide improvements in road safety planning. This study aims to provide a built environmental analysis of road traffic crash hotspots within Moshi, Tanzania.

Methods After ethical and police permission, Moshi police data was collected and descriptive statistics were tabulated. Hotspots were identified through spatial analysis and relevant patterns in environmental characteristics determined using Qualitative Comparative Analysis (QCA).

Results 36 Hotspots were identified. QCA revealed 40% of crash sites were found on local roads, without night lighting and had increased motorcycle density. A further 26% of hotspots were located on paved narrow roads and 13% of hotspots were described as unpaved roads with uneven roadside areas. Roadside unevenness was more predominate in low risk sites, (High risk $n = 7$ (46.7%), Low risk $n = 19$, 90.5%, $p = 0.01$). Both low and high risk sites had minimal signage (High risk $n = 1$ (6.7%), low risk $n = 6$ (28.6%) and all had informal pedestrian pathways (High risk $n = 15$ (100%), low risk $n = 21$ (100%) .

Conclusions In Moshi, Tanzania hotspots were associated with roadside dangers, lack of night lighting, informal pedestrian pathways, and increased traffic density but overall there was little variability between the low and high risk sites suggesting hazardous road conditions exist throughout the area. Our findings suggest overall improvement in municipal infrastructure, including structural improvements, signage and enforcement are needed to help reduce road traffic injury burden.

872

WHY UNSAFE AND VULNERABLE HIGHWAY IN BANGLADESH?

Soyab Ali. Dhaka Metropolitan Police (DMP), Bangladesh Trainer on Defensive Driving and Occupational Safety

10.1136/injuryprev-2016-042156.872

Background Safe Highway is a multifunctional issue and requires more attention to reduce the ever increasing of road crashes and accidents. Vehicles using National and Regional Highways (NRH) in Bangladesh have a wide variation in operating characteristics with a combination of motorised and non-motorised form of transports such as farm tractors, animal carts; tricycles taxis (Rickshaw) which share the same road of first moving motorize traffic. There are thousands of roadside markets and other infrastructures which dangerous and threat In addition extensive practices of pedestrians Jaywalking and illegal road crossing by foot due to lack of overhead crossing often contribute to cause. Pedestrian activity is also high in these stretches. Considering all these in mind and to make the Highways safer, we have to take integral program combining the every component responsible for safety issue.

Methods Use Police HQ MAPS data/Accident Research Centre (ARC) library and Bangladesh Road Transport Authority (BRTA) annual report, 2014-15 and newspaper cutting.

Results Road worthy vehicles can reduce accidents & congestion in great number. Chaotic traffic movement and congestion on road are very common in Bangladesh is rated 15 one of the high risk country in the world. There are thousands of roadside markets and other infrastructures which dangerous and threat. As a cost on an average 12–14 people killed every day and annually 4200 on and average which affect 1.8% of GDP.

Cars, buses and trucks frequently drive at high speed without headlights illuminated or on full beam. Drivers overtake other vehicles at inappropriate moments and causes head-on collisions.

Conclusions We need to educate the citizens, require strong political commitment from government and provide proper facilities to avoid road accident and loss of life by traffic crash.

Components in Highways there are about 3886 km National Highway and 1751 km Regional Highway in our country owned

by Roads and Highways Division-RHD. There are few Highways in Bangladesh, which cover International Standard. Only recently build few Highways only fulfilled few criteria of international quality

Mix Traffic using highways and local made poor standard vehicle like local made nonmotorized transport, Human Pulling Rickshaw, Bicycle, horse and bull carts.

Roadside Markets like shops, village market, Hawkers, work-shops, mosque and schools

Other infrastructure bi-lane, shoulder, road makings, median road signs, uneven surface, straight sub-lane, small shoulder and without road shoulder, muddy side road, poor design of median, poor road markings, poor road signs are common phenomenon of our existing highways.

873

GOALS FOR RIDER EDUCATION: ADAPTATION OF FINNISH GOALS FOR DRIVER EDUCATION MODEL FOR MOTORCYCLISTS

¹Teresa Senserrick, ²Duncan McRae, ³Phil Wallace, ¹Ann Williamson, ⁴Liz de Rome. ¹University of New South Wales, Australia; ²Youthsafe, Australia; ³Learning Systems Analysis, Australia; ⁴LdeR Consulting, Australia

10.1136/injuryprev-2016-042156.873

Background The authors were commissioned to develop education curricula for a new motorcyclist graduated licensing system in Victoria, Australia. A review of published literature identified several promising models internationally, but no single best-practice framework. The objective of this research was to determine whether a best-practice framework implemented for new drivers, the Finnish Goals for Driver Education (GDE; Keskinen, 1996), could be adapted and applied for new motorcyclists. The model comprises four levels: basic, tactical, strategic and general.

Methods An adapted framework was drafted by replacing driver-specific content to motorcyclist-equivalent content where applicable (e.g. seatbelts to helmets). Curriculum materials were drafted using the framework as a guide, focusing on the five most frequent novice motorcyclist crash types in Victoria and particularly enhancing the roadcraft content of the tactical and strategic levels. Train-the-trainer pilots were offered to experienced motorcycle trainers with one medium-sized provider in Victoria, and the option to undertake the pilot programs offered to their learner permit and licence candidates on selected weeks in March to October 2015. Student pilots were conducted to saturation, that is, until no new feedback was obtained. University Ethics approval was obtained.

Results In total, 10 trainers and 53 students took part in the pilots. Saturation was achieved in 6 pilots each for pre-learner course, and combined learner and licence course components. Feedback from participants showed strong support for the curriculum and suggested that all levels of the model had been addressed.

Conclusions The results suggested that the GDE model had been readily adapted into a promising framework for improving novice motorcyclist education. The Victorian Government has commenced plans to conduct a pre-post outcome evaluation of the new curriculum, which is due to commence rollout across the state in March 2016.