

Risk of injury for bicycling on cycle tracks versus in the street

Anne C Lusk,¹ Peter G Furth,² Patrick Morency,^{3,4} Luis F Miranda-Moreno,⁵ Walter C Willett,^{1,6} Jack T Dennerlein^{7,8}

¹Department of Nutrition, Harvard School of Public Health, Boston, MA USA

²Department of Civil and Environmental Engineering, Northeastern University, Boston, MA USA

³Direction de santé publique de Montréal, Montréal, Québec, Canada

⁴Département de Médecine Sociale et Préventive, Université de Montréal, Montréal, Québec, Canada

⁵Department of Civil Engineering and Applied Mechanics, McGill University, Montréal, Québec, Canada

⁶Department of Epidemiology, Harvard School of Public Health, Boston, MA, USA

⁷Department of Environmental Health, Harvard School of Public Health, Boston, MA, USA

⁸Department of Orthopaedic Surgery, Brigham and Women's Hospital, Harvard Medical School, Boston, MA, USA

Correspondence to

Dr Anne Lusk, Harvard School of Public Health, 665 Huntington Avenue, Building II, Room 314, Boston, MA 02115, USA; annelusk@hsph.harvard.edu

Accepted 1 December 2010

ABSTRACT

Most individuals prefer bicycling separated from motor traffic. However, cycle tracks (physically separated bicycle-exclusive paths along roads, as found in The Netherlands) are discouraged in the USA by engineering guidance that suggests that facilities such as cycle tracks are more dangerous than the street. The objective of this study conducted in Montreal (with a longstanding network of cycle tracks) was to compare bicyclist injury rates on cycle tracks versus in the street. For six cycle tracks and comparable reference streets, vehicle/bicycle crashes and health record injury counts were obtained and use counts conducted. The relative risk (RR) of injury on cycle tracks, compared with reference streets, was determined. Overall, 2.5 times as many cyclists rode on cycle tracks compared with reference streets and there were 8.5 injuries and 10.5 crashes per million bicycle-kilometres. The RR of injury on cycle tracks was 0.72 (95% CI 0.60 to 0.85) compared with bicycling in reference streets. These data suggest that the injury risk of bicycling on cycle tracks is less than bicycling in streets. The construction of cycle tracks should not be discouraged.

Bicycling could address obesity, cancer, stroke, diabetes, asthma, mortality and pollution;^{1 2} however, the bicycling environment is a limiting factor. The predominant bicycle facilities in The Netherlands and Denmark are cycle tracks, or bicycle paths along streets that are physically separated from motor traffic, bicycle-exclusive and with a parallel sidewalk.³ Due to the separation from vehicles afforded by 29 000 km of cycle tracks in The Netherlands plus other initiatives,⁴ 27% of Dutch trips are by bicycle, 55% are women, and the bicyclist injury rate is 0.14 injured/million km.⁵ In the USA, 0.5% of commuters bicycle to work, only 24% of adult cyclists are women,⁶ and the injury rate of bicyclists is at least 26 times greater than in The Netherlands.⁵ The chief obstacle to bicycling, especially for women,⁷ children⁸ and seniors⁹ is perceived danger of vehicular traffic. This perceived danger from cars appears to be real,¹⁰ as corroborated by survey participants who prefer cycle tracks over roads.¹¹

Cycle track construction has been hampered in the USA by engineering guidance in the American Association of State Highway and Transportation Officials (AASHTO) 'Guide for the development of bicycle facilities'¹² which cautions against building two-way paths along, but physically separated from, a parallel road. AASHTO states that sidewalk bikeways are unsafe and implies the same about shared-use paths parallel to roads, listing numerous

safety concerns and permitting their use only in special situations. Cycle tracks, which can be one or two-way and resemble shared-use paths, are not mentioned in the AASHTO bike guide. A long-standing, and yet not rigorously proved, philosophy in the USA has suggested instead that 'bicyclists fare best when they behave as, and are treated as, operators of vehicles.'¹³ The details about cycle tracks in the Dutch bicycle design manual CROW³ and crash rate comparisons between the USA and The Netherlands⁵ have been dismissed by vehicular cycling proponents,¹⁴ with arguments of non-transferability to the American environment. Cycle tracks have been controversial, especially due to conflicting studies with warnings of increased crash rates.¹⁵ The warnings, which in the USA result in striped bike lanes but not cycle tracks, come without any substantial study of the safety of North American cycle tracks. Using existing crash and injury data from Montreal, Canada, a city with a network of cycle tracks in use for more than 20 years, this study compared bicyclists' injury and crash rates with published data and bicyclists' injury rates on cycle tracks versus in the street.

METHODS

We studied six cycle tracks in Montreal that are two-way on one side of the street. Each cycle track was compared with one or two reference streets without bicycle facilities that were considered alternative bicycling routes. One reference street was a continuation of the street with the cycle track; the remaining streets were parallel to the cycle track with the same cross streets as endpoints and, therefore, subject to approximately the same intersection frequency and cross traffic as the cycle track.

Injury and vehicle/bicycle crash rates per bicycle-kilometre

The injury and crash rates for each cycle track were determined from the emergency medical response (EMR) database¹⁶ and police-recorded vehicle/bicycle crashes and estimated on the cycle tracks per bicycle-km. Automated 24-h bicycle counts on Montreal cycle tracks are available for selected years, with 20–64 days in each sample from May to September. We used linear interpolation between the 2000 and 2008 samples to determine average daily use for the date ranges of the injury and crash counts. Average daily use was converted to annual use by multiplying by 200 'effective days' in the 1 April to 15 November bicycling season (when seasonal cycle tracks are open), recognising that



This paper is freely available online under the BMJ Journals unlocked scheme, see <http://ip.bmj.com/site/about/unlocked.xhtml>

bicycle use tends to be less in April, October and November than in the sampled months. Use estimates were converted to bicycle-km by multiplying by segment length and the fraction of the cycle track's length ridden per cyclist. This fraction, which ranged from 0.6 to 0.9, was determined using expert judgement considering the cycle track length and opportunities for turning on and off.

Relative Risk (RR) of injury for cycle tracks

The RR of the cycle track compared with the reference street was estimated using bicyclist counts and injuries from the EMR database.¹⁶ Although injury (EMR) and bicycle/vehicle crash data from police records overlap strongly, the injury data have been shown to be more exhaustive¹⁷ and were available for a longer period. Injury counts were determined for the 1 April to 15 November bicycling season and within 15 m of each street centerline. For comparability with exposure data, it was important to exclude individuals injured at intersections who may have been riding on a cross street; however, the EMR database does not indicate which street the injured cyclist was using. Therefore, using the police crash database we determined for each section studied the fraction of bicycle/vehicle crashes involving cyclists who were riding on cross streets, and reduced injury counts by that fraction.

Historical bicycle counts were available for the cycle tracks but not the reference streets. To obtain an unbiased measure of relative exposure, simultaneous 2 h bicycle counts were conducted at parallel counting sites on each cycle track and its reference street(s). Using a ratio of simultaneous counts eliminates systematic effects on bicycle use such as weather, time and day. The simultaneous counts were made during mild weather commuting hours in 2009.

The RR of injury for each cycle track was calculated as:

$$RR = \frac{\frac{\text{injuries}_{\text{track}}}{\text{bikes}_{\text{track}}}}{\frac{\text{injuries}_{\text{ref}}}{\text{bikes}_{\text{ref}}}}$$

where injuries_{track} and injuries_{ref} are the count of injuries on the cycle track and reference street(s), respectively, and bikes_{track} and bikes_{ref} are the corresponding cyclist counts.

Ninety-five percent CI were calculated using the variance of log(ratio) based on a Poisson distribution for incidents. CI that did not include 1 were considered statistically significant. RR for all cycle tracks was calculated similarly using the summed data from all the observations.

Relative danger from vehicular traffic

Reference streets were selected with vehicular traffic danger (volume, speed, heavy vehicles) as similar as possible to their cycle track; however, it was impossible to achieve exact similarity. Therefore, to compare the vehicular traffic danger, we also calculated the ratio of motor vehicle occupant (MVO) injuries on the cycle track street to MVO injuries on the reference street. MVO injury counts are considered a surrogate for traffic danger a bicyclist might face on a given street apart from any treatment.

RESULTS

All six cycle tracks were two-way on one side of the street and separated from traffic by raised medians, parking lanes, or delineator posts. There were 8.5 injuries and 10.5 crashes per million bicycle-km. The Brébeuf and Maisonneuve cycle tracks stand out as safer than the other four (table 1).

Table 1 Injury and vehicle/bicycle crash rates for cycle tracks in Montreal, Quebec*

Cycle track	Configuration	Separation	Length† (km)	Length‡ factor#	Cyclists/day, 1999–2008 §	Bike-km/year (millions) ¶ **	Injuries/ year ††	Crashes/ year †††	Injuries per million bike-km	Crashes per million bike-km
1. Brébeuf (seasonal)	2-Way, 1 side of one-way street, street level	Delineator posts and parking lane	1.0	0.9	5316	0.96	3.9	1.8	4.1	1.9
2. Rachel	2-Way, 1 side of two-way street, street level	Raised median, delineator posts, parking lane	3.5	0.6	2581	1.08	12.6	17.0	11.6	15.7
3. Berri	2-Way, 1 side of two-way street, street/sidewalk level	Raised median, delineator posts, and parking lane	1.4	0.8	2778	0.62	7.8	10.2	12.5	16.4
4. Maisonneuve, w. island (seasonal)	2-Way, 1 side of one-way street, street level	Delineator posts	1.9	0.9	2379	0.81	1.9	2.6	2.3	3.2
5. Chr Colombe (seasonal)	2-Way, 1 side of two-way street, sidewalk level	Curb and (part) planting strip	3.7	0.7	921	0.48	6.7	9.2	14.1	19.3
6. René-Levesque	2-Way, 1 side of two-way street, street level	Raised median, delineator posts, parking lane	1.3	0.8	1108	0.23	2.8	3.2	12.3	13.9
All						4.18	35.7	44.0	8.5	10.5

*Whole segments of the cycle track were studied and not just intersections.
 †Length of the section studied, which may be less than the entire cycle track length for comparability with reference streets.
 ‡Fraction of the study section's length ridden by a typical rider.
 §Average for the May to September period over the period 1999–2008.
 ¶'Year' is the 7.5 month period (1 April to 15 November) when the seasonal cycle tracks are open.
 **Demand is lower in April, October and November and, therefore, bicycle volume for a 'year' is assumed to be 200 times the daily volume.
 ††Injuries (data source — emergency medical response) between 1 April and 15 November for the period 1 April 1999 to 31 July 2008 divided by 9.53.
 †††Bicycle—motor vehicle crashes (data source — police reports) between 1 April and 15 November 2002–6, divided by 5.

Table 2 RR of injury for cycle tracks compared to similar on-street routes for Montreal, Quebec*

Cycle track†	Reference street‡	Limiting cross streets	Length (km)	Cycle track		Reference street		RR (95% CI)¶
				2-h bike count	EMR-reported injuries§	2-h bike count	EMR-reported injuries§	
1. Brébeuf	St Denis (N)	Rachel – Laurier	1.0	1193	37	437	32	0.42 (0.26 to 0.68)
2. Rachel	Mont Royal	St Urbain – Marquette	3.5	990	120	613	63	1.18 (0.87 to 1.60)
3. Berri	St Denis (S)	Cherrier – Viger	1.4	763	74	134	27	0.48 (0.31 to 0.75)
4. Maisonneuve	Both	Claremont – Wood	1.9	547	18	176**	18	0.32 (0.17 to 0.62)
	Sherbrooke (W)					129	14	0.30
	Ste Catherine					47	4	0.39
5. Christophe Colomb	Both	Gouin – Jarry	3.7	407	64	122	19	1.01 (0.61 to 1.68)
	Saint-Hubert					45	9	0.79
	Christophe Colomb (S)	Villeray – Rosemont	2.3			77	10	1.21
6. René Levesque	Sherbrooke (E)	Lorimier – St Hubert	1.3	109	27	130	32	1.01 (0.60 to 1.68)
All			15.1	4009	340	1612	191	0.72 (0.60 to 0.85)

*Statistically significant comparisons are shown in **bold**.

†All cycle tracks are two-way on one side of the street.

‡An on-street bike route on a parallel street in close proximity of the cycle track.

§Injuries recorded by emergency medical response (EMR) services between 1 April 1999 and 31 July 2008 for the season 1 April to 15 November.

¶95%CI calculated using the variance of log(RR) based on a Poisson distribution.

**For comparisons having two reference streets, the total number of bicyclists is used from both streets.

Compared with bicycling on a reference street, the overall RR of injury on a cycle track was 0.72 (95% CI 0.60 to 0.85); thus, these cycle tracks had a 28% lower injury rate. Three of the cycle tracks exhibited RR less than 0.5, and none showed a significantly greater risk than its reference street. Overall, 2.5 times as many cyclists used the cycle tracks compared with the reference streets (table 2).

The relative danger from vehicular traffic of the cycle tracks compared with their reference streets was close to 1.0 overall, but with a wide range (table 3). Not surprisingly, the Brébeuf and Maisonneuve cycle tracks with lowest crash rate and relative injury risk (tables 1 and 2) also had the lowest relative danger from vehicular traffic (table 3). Yet even for the four cycle tracks on streets with vehicular traffic danger similar to or greater than its reference street, the cycle tracks still had less or a similar risk of injury.

DISCUSSION

Contrary to AASHTO's safety cautions about road-parallel paths and its exclusion of cycle tracks, our results suggest that two-way cycle tracks on one side of the road have either lower

or similar injury rates compared with bicycling in the street without bicycle provisions. This lowered risk is also in spite of the less-than-ideal design of the Montreal cycle tracks, such as lacking parking setbacks at intersections, a recommended practice.¹⁸

While the goal of this study was to consider both one and two-way cycle tracks, all of the Montreal cycle tracks were two-way with half the bicyclists riding in a direction opposite to that of the closest vehicular traffic, a practice not favoured by AASHTO. Although the Montreal cycle tracks were two-way, they had lower or similar risk compared with the road. The Dutch CROW bicycle guidelines suggest that one-way cycle tracks are even safer.³

The crash rate for Montreal's cycle tracks (10.5 crashes per million bicycle-km) is low compared with the few and inconsistent crash rates in the literature. When calculated to include only vehicle/bicycle crashes, these rates range from 3.75⁵ to 54¹⁹ in the USA and from 46²⁰ to 67²¹ in Canada. The injury rate (8.5 injuries per million bicycle-km) lacks comparable data in the literature, partly because few communities have accessible bicycle-incident ambulance records. Although the Brébeuf and Maisonneuve cycle tracks were safer, the sample of six cycle

Table 3 Relative danger from vehicular traffic*

Cycle track street	Reference street	MVO injuries†		Relative traffic danger of cycle track street (95% CI)‡
		Cycle track street	Reference street	
1. Brébeuf	St Denis (N)	8	90	0.09 (0.04 to 0.18)
2. Rachel	Mont Royal	86	69	1.25 (0.91 to 1.73)
3. Berri	St Denis (S)	127	116	1.09 (0.85 to 1.41)
4. Maisonneuve	Both	13	59§	0.22 (0.12 to 0.40)
	Sherbrooke (W)		72	
	Ste Catherine		46	
5. Christophe Colomb	Both	367	217§	1.69 (1.43 to 2.00)
	Saint-Hubert		268	
	Christophe Colomb (S)		166	
6. René Levesque	Sherbrooke (E)	196	205	0.96 (0.79 to 1.16)
All	All	797	756	1.05 (0.95 to 1.16)

*Statistically significant comparisons are shown in **bold**.

†Injuries to motor vehicle occupants recorded by emergency medical response (EMR) services between 1 January 1999 and 31 July 2008.

‡95% CI calculated using the variance of log(RR) based on a Poisson distribution.

§For comparisons having two reference streets, the average number of injuries of the reference streets is used. MVO, motor vehicle occupant.

Table 4 Crash RR from Wachtel and Lewiston²² data with non-intersection crashes included*

	Sidewalk		Roadway		All		RR, sidewalk versus in-street (95% CI)†	p Value‡
	Riders	Crashes	Riders	Crashes	Riders	Crashes		
Intersection only§								
All cyclists	971	41	2005	48	2976	89	1.76 (1.16 to 2.68)	0.01
Bicycling in same direction as closest traffic lane	656	13	1897	43	2553	56	0.87 (0.47 to 1.63)	0.56
All crashes¶								
All cyclists	971	41	2005	79	2976	120	1.07 (0.73 to 1.56)	0.79
Bicycling in same direction as closest traffic lane	656	13	1897	71	2553	84	0.53 (0.29 to 0.96)	0.02

*Statistically significant comparisons are shown in **bold**.

†95% CI calculated using the variance of log(IRR) based on a Poisson distribution.

‡Significance, calculated using the variance of log(IRR) based on a Poisson distribution (for comparison with original article).

§Authors' original data.

¶Non-intersection crashes amounting to 26% of total crashes added to roadway crashes.

tracks was too small to determine which factors make some safer.

In one of the few comparisons of bicycling in the street versus bicycling on a separated path parallel to the street in the USA, Wachtel and Lewiston²² determined a relative crash risk of 1.8 for bicycling on sidewalks which had been designated as bike-ways, compared with bicycling in the adjacent street in Palo Alto, California. However, their study considered only intersection crashes, omitting non-intersection crashes that include being hit from behind, sideswiped, or struck by a car door. The authors, though, reported that 26% of cyclist–motor vehicle collisions city-wide in Palo Alto were non-intersection crashes. If non-intersection crashes are included to match this 26% proportion, reanalysis of the Wachtel and Lewiston²² data in the article shows that there is no significant difference in risk between the sidewalk bikeway and the street (table 4). For bicyclists riding in the same direction as traffic, as would be case with one-way cycle tracks, sidewalk bikeways carried only half the risk of the street. Therefore, the Wachtel and Lewiston²² data, when corrected to include non-intersection crashes, corroborate our findings that separated paths are safer or at least no more dangerous than bicycling in the street. Furthermore, as the most common cause of fatal bicyclist collisions in urban areas is overtaking,²³ it is probable that an analysis accounting for the severity of injury would be still more favourable towards cycle tracks.

Our study considered whole segments of cycle tracks and not just intersections, measured bicycle exposure directly, and included appropriate comparison groups. The study, though, only included analysis of six cycle tracks, all of which were two-way and in the same city, and lacked injury severity data. This

What is already known on this subject

- ▶ Individuals, in particular women, children, and seniors, prefer to bicycle separated from motor traffic.
- ▶ Cycle tracks (physically-separated bicycle-exclusive paths along roads) exist and continue to be built in The Netherlands where 27% of all trips are by bicycle and 55% of bicycle riders are female.
- ▶ Engineering guidance in the United States has discouraged bicycle facilities that resemble cycle tracks, including parallel sidepaths and sidewalk bikeways, suggesting that these facilities and cycle tracks are more dangerous than bicycling in the street.

What this study adds

- ▶ Overall, 2 ½ times as many cyclists rode on the cycle tracks compared with the reference streets.
- ▶ There were 8.5 injuries and 10.5 crashes per million-bicycle kilometers respectively on cycle tracks compared to published injury rates ranging from 3.75 to 67 for bicycling on streets. The relative risk of injury on the cycle track was 0.72 (95% CI=0.60-0.85) compared with bicycling in the reference streets.
- ▶ Cycle tracks lessen, or at least do not increase, crash and injury rates compared to bicycling in the street.

research underscores the need for better bicycle counting and injury surveillance and for additional safety studies, particularly of one-way cycle tracks, intersections, injury severity and other factors that affect cycle track safety.

IMPLICATIONS FOR POLICY

Public health and bicycling advocates in the USA have faced a dichotomy, believing from surveys and European experience that cycle tracks encourage more bicycling, yet being warned that they lead to higher crash and injury rates. Our results suggest that cycle tracks lessen, or at least do not increase, crash and injury rates compared with the street. The construction of cycle tracks should not be discouraged.

Acknowledgements The authors would like to thank Kevin Manaugh (McGill University) and Nathalie Valois (Montreal police), who performed the geographical queries to extract data from the crash database, and Qi Sun and Elaine Hoffman for a review of the statistics.

Funding ACL was supported by a Ruth L Kirschstein National Research Service Award, F32 HL083639 from the National Institutes for Health, National Heart, Lung and Blood Institute. LFM-M is supported for data collection by the Natural Sciences and Engineering Research Council of Canada (discovery grant — individual).

Competing interests None.

Ethics approval The Harvard School of Public Health IRB reviewed this protocol and found that approval was not required. The HSPH IRB made an exemption determination.

Contributors PGF had full access to the data in the study and takes responsibility for the integrity of the data and the accuracy of the data analysis. Conception and design: ACL and PGF. Acquisition of data: ACL, PGF, PM and LFM-M. Analysis and interpretation of data: ANL, PGF, PM, LFM-M, WCW and JTD. Drafting of manuscript: ACL, PGF. Critical revision for intellectual content: ACL, PGF, PM, LFM-M, WCW and JTD. Statistical expertise: ACL, PGF, PM, LFM-M, WCW and JTD. Administrative, technical or material support: WCW. Study supervision: PGF, WCW and JTD.

Provenance and peer review Not commissioned; externally peer reviewed.

REFERENCES

1. **Lusk AC**, Mekary RA, Feskanich D, *et al*. Bicycle riding, walking, and weight gain in premenopausal women. *Arch Intern Med* 2010;**170**:1050–6.
2. **Andersen LB**, Schnohr P, Schroll M, *et al*. All-cause mortality associated with physical activity during leisure time, work, sports, and cycling to work. *Arch Intern Med* 2000;**160**:1621–8.
3. **CROW**. *Design manual for bicycle traffic*. Netherlands: National Information and Technology Platform for Infrastructure, Traffic, Transport, and Public Space, 2006.
4. Verkeersnet.nl. Fietsersbond: Veel meer fietspad dan bekend in ons land. 2009. <http://www.verkeersnet.nl/1782/fietsersbond-veel-meer-fietspad-dan-bekend-in-ons-land/> (accessed 21 Apr 2010).
5. **Pucher J**, Buehler R. Making cycling irresistible: lessons from the Netherlands, Denmark, and Germany. *Transport Reviews* 2008;**28**:1–34.
6. **U.S. Census Bureau**. *American community survey 3-year estimates B08006 sex of workers by means of transportation to work — universe — workers 16 years and over*. 2006–2008. http://factfinder.census.gov/servlet/DTable?_bm=y&-geo_id=01000US&-ds_name=ACS_2008_3YR_G00_8_-lang=en&-caller=geoselect&-state=dt&-format=&-mt_name=ACS_2008_3YR_G2000_B08006 (accessed 26 Jan 2010).
7. **Garrard J**, Rose G, Lo SK. Promoting transportation cycling for women: the role of bicycle infrastructure. *Prev Med* 2008;**46**:55–9.
8. **Mehan TJ**, Gardner R, Smith GA, *et al*. Bicycle-related injuries among children and adolescents in the United States. *Clin Pediatr (Phila)* 2009;**48**:166–73.
9. **Hayes JS**, Henslee B, Ferber J. Bicycle injury prevention and safety in senior riders. *J Trauma Nurs* 2003;**10**:66–8.
10. **Haileyesus T**, Annett JL, Dellinger AM. Cyclists injured while sharing the road with motor vehicles. *Inj Prev* 2007;**13**:202–6.
11. **Winters M**, Teschke K. Route preferences among adults in the near market for bicycling: findings of the cycling in cities study. *Am J Health Promot* 2010;**25**:40–7.
12. **American Association of State Highway and Transportation Officials**. *Guide for the development of bicycle facilities*. Washington, DC: AASHTO, 1999.
13. **Forester J**. *Effective cycling*. Cambridge: The MIT Press, 1984.
14. **Forester J**. *The bikeway controversy*. *Transportation Quarterly*. Washington, D.C., USA, Spring, 2001:55.
15. **Jensen S**. Bicycle tracks and lanes: a before-and-after study. *Transportation Research Board 87th Annual Meeting, 2008-1-13 to 2008-1-17*. Washington, DC, 2008:15.
16. **Morency P**, Cloutier MS. From targeted “black spots” to area-wide pedestrian safety. *Inj Prev* 2006;**12**:360–4.
17. **Langley JD**, Dow N, Stephenson S, *et al*. Missing cyclists. *Inj Prev* 2003;**9**:376–9.
18. **Velo Quebec**. *Technical handbook of bikeway design*. 2nd ed. Quebec: Ministère des Transport du Québec and the Secretariat au Loisir et au Sport, 2003.
19. **Dennerlein JT**, Meeker JD. Occupational injuries among Boston bicycle messengers. *Am J Ind Med* 2002;**42**:519–25.
20. **Aultman-Hall L**, Hall FL. Ottawa—Carleton commuter cyclist on- and off-road incident rates. *Accid Anal Prev* 1998;**30**:29–43.
21. **Aultman-Hall L**, Kaltenecker MG. Toronto bicycle commuter safety rates. *Accid Anal Prev* 1999;**31**:675–86.
22. **Wachtel A**, Lewiston D. Risk factors for bicycle-motor vehicle collisions at intersections. *ITE Journal of Institute of Transportation Engineers* 1994:30–5.
23. **McCarthy M**, Gilbert K. Cyclist road deaths in London 1985–1992: drivers, vehicles, manoeuvres and injuries. *Accid Anal Prev* 1996;**28**:275–9.